

specifications



Model	T101 / T101c	T301 / T301c	T-2
Design	Two-way closed box	Two and a half-way closed box	Closed box powered subwoofer
Drive units	115mm (4.5in.) dual layer MF 25mm (1in.) aluminium HF	2 x 115mm (4.5in.) dual layer MF 25mm (1in.) aluminium HF	1 x 250mm (10in.)
Frequency response	80Hz - 30kHz	80Hz - 30kHz	30Hz - 250Hz
Crossover frequency	1.7kHz	1.7kHz	N/A
Amplifier	N/A	N/A	250 Watts built-in Class-D
Amplifier requirements	10 - 100 W	10 - 150 W	N/A
Sensitivity (2.83V/1m)	90dB (wall mount) 87dB (floor stand mount)	91dB (wall mount) 88dB (floor stand mount)	N/A N/A
Maximum output (SPL)	107dB	110dB	110dB
Impedance	8Ω	8Ω	N/A
Low pass filter variable	N/A	N/A	Fixed 250Hz, 2nd-order
Low level signal inputs	N/A	N/A	RCA phono socket
Internal volume	0.7 Litres	1.4 Litres	12.7 Litres
Power requirements	N/A	N/A	100 - 240 V ac ~ 50/60Hz
Power consumption	N/A	N/A	250VA
Weight	1 kg (2.2lbs)	1.5kg (3.3lbs)	13kg (28.6lbs)
Dimensions (H x W x D)	330* x 140 x 35 mm (13.0 x 5.5 x 1.4 in.)	600* x 140 x 35 mm (23.6 x 5.5 x 1.4 in.)	380 x 370 x 177 mm (15.0 x 14.6 x 7.0 in.)
Dimensions (H x W x D) center mode	140 x 330 x 35 mm (5.5 x 13.0 x 1.4 in.)	140 x 600 x 35 mm (5.5 x 23.6 x 1.4 in.)	N/A N/A
Finish	Black	Black	Black

* Height of satellites will increase by 30mm when using supplied desk stand

Not all models / finishes are available in all markets. Contact your local dealer for specific range details.