



MARK LEVINSON N°5101

The N°5101 combines decades of superlative audio engineering with the latest technological advancements to deliver unmatched performance and value.

With a bold new industrial design, the N°5101 delivers luxurious fidelity with premium features and flexibility. Combining audiophile physical compact disc formats with modern high-resolution network streaming capabilities over Ethernet and WiFi, a standalone PrecisionLink II DAC, and expansive control features, the N°5101 is a unique 3-in-1 solution.

DIGITAL AUDIO

The N°5101 delivers outstanding digital audio capability with the Mark Levinson PrecisionLink II DAC. Five individual, ultra-low-noise voltage regulators, power an ESS Sabre 32-bit PRO series D/A converter to unleash maximum performance. Proprietary jitter reduction circuitry and user-selectable digital filters—seven choices for PCM and four for DSD along with ample regulated power, enables the best possible digital reproduction.

The N°5101 offers a variety of digital inputs, including one coaxial and one optical S/PDIF; one USB-A for playback from a thumb drive or hard drive, a CD/SACD transport and network streaming via Wi-Fi or Ethernet.

FLAC, WAV, AIFF, OGG, MP3, AAC and WMA, audio formats, and SACD, CD-A, CD-R, and CD-RW disc formats are supported.

ANALOG OUTPUT STAGE

The N°5101 utilizes proprietary Mark Levinson PurePath circuitry. Fully discrete, direct-coupled, dual-monaural line-level output circuitry delivers exceptional reproduction of the analog signal to the balanced XLR stereo outputs as well as the single-ended RCA connectors. The linear power supply and toroidal transformer with separate voltage regulators for the left and right channels provide a quiet, stable source of power for critical analog circuitry.

CONTROL

System integration and communication ports include IP (Ethernet), RS-232, IR input, and 12V trigger input. A newly designed, aluminum IR remote is included with the N°5101. In addition, the Mark Levinson 5kontrol mobile application enables control from an available Android and iOS device, and drivers are available for major control systems.

INDUSTRIAL DESIGN

Robust materials, lavish finishes, and bold geometry are hallmark attributes of Mark Levinson designs. The one-inch thick, bead-blasted, black-anodized, solid aluminum front panels are machined and contoured to flow seamlessly into the sleek glass display, which itself is recessed into a bead-blasted, clear-anodized aluminum bezel. With debossed top cover vents, screen-printed logo, and machined aluminum buttons, no detail has been overlooked.

The Mark Levinson N°5101 is proudly designed, engineered, and precision-crafted in the USA.



Performance Specifications

MARK LEVINSON N°5101



All production N°5101 units will undergo 100% functional testing prior to shipment, and the following features and electrical measurements will be verified on all units.

Output voltage:	3.0V RMS single-ended at full scale (0dBFS) 6.0V RMS balanced at full scale (0dBFS)	Output connectors:	1 pair single-ended line-level outputs (RCA) 1 pair balanced line-level outputs (XLR)
Total harmonic distortion + noise:	<0.004%, 20Hz to 20kHz, single-ended, 3V RMS output (44.1kHz/16 bit signal) <0.003%, 20Hz to 20kHz, balanced, 6V RMS output (44.1kHz/16 bit signal) <0.003%, 20Hz to 20kHz, single-ended, 3V RMS output (192kHz/24 bit signal) <0.002%, 20Hz to 20kHz, balanced, 6V RMS output (192kHz/24 bit signal)	Control and network connectors:	1 RS-232 port (DB9 connector) 1 IR input (1/8"/3.5mm phone jack) 1 12V DC trigger input (1/8"/3.5mm phone jack) 1 Ethernet port (RJ-45 connector) 1 USB-A connector 1 Wi-Fi antenna connector (SMA receptacle)
Signal-to-noise ratio:	>94dB single-ended (wideband, unweighted, referred to 3V RMS output) >106dB balanced (wideband, unweighted, referred to 6V RMS output)		
Power consumption:	Standby: <0.4W Power on: 32W		
Digital audio connectors:	1 optical digital input (Toslink) 1 coaxial digital S/PDIF input (RCA) 1 optical digital output (Toslink) 1 coaxial digital S/PDIF output (RCA)		



HARMAN International Industries, Incorporated
8500 Balboa Boulevard, Northridge, CA 91329
marklevinson.com

©2020 HARMAN International Industries, Inc. Mark Levinson and the Mark Levinson logo are trademarks of HARMAN International Industries, Inc., registered in the United States and other countries. All rights reserved. Features, specifications and appearance are subject to change without notice.