

DALI PHANTOM

M-675

PREMIUM IN-WALL HIFI LOUDSPEAKER

The PHANTOM M-675 is a large and slim high-performance in-wall speaker designed for high-end/high performance CI home-cinema installations, and features eight drive units, all developed in-house for the very best sound quality.

AMAZING SOUND QUALITY

The PHANTOM M-675 uses two SMC based 7 inch bass midrange drivers and four 7 inch passive radiators for an extended low frequency response, higher SPL and higher power handling. Everything on the M-675 is developed by DALI in Denmark for amazing sound quality.

INTEGRATED BACKBOX

The fully closed cabinet makes installation extremely easy without the need for a backbox. The speaker is ready for mounting out-of-the-box, with no additional accessories needed. With the optional On Wall Frames, The M-675 can also be mounted on the wall in a stylish and discrete way that is quite unique in the market.

EASY INSTALLATION

The M-675 is installed using the ten integrated doglegs. These are high quality manual doglegs, ensuring firm installation to avoid any rattling. The Hybrid Tweeter Module can also be rotated, for optimum horizontal dispersion when used as a centre channel, mounted horizontally below or above the screen.

DISCRETE DESIGN

Magnetic grilles are included in the box and are fully paintable for customization to fit every room. The M-675 offers a slimmer profile than our PHANTOM S series, making installation below or to the sides of a TV more easy on the eyes and guarantees high performance in an elegant and slim enclosure.

The DALI logo consists of the word "DALI" in white, uppercase letters, centered within a solid red square.

IN ADMIRATION OF MUSIC

TECHNICAL SPECIFICATIONS

M-675

Frequency Range (+/-3 dB)	49 - 25,000 Hz
Sensitivity (2.83V/1 m)	90 dB
Nominal Impedance	4 ohm
Maximum SPL	110 dB
Crossover Frequency	1,000 / 2,800 / 15,000 Hz
Recommended Amplifier Power	40 - 300 Watt
High Frequency Driver	1 x 28 mm soft dome 1 x 17 x 45 mm ribbon
Low/Mid Frequency Driver	2 x 7 inch Wood fibre cone
Connection Input	Single wire
Enclosure Type	Closed box, 4 x 7 inch passive radiators
Recommended placement	Front / Centre / Rear / Surround
Functions	Normal / HF+
Dimensions (H x W x D)	1322 x 250 x 106 mm 52 x 9.8 x 4.1 in
Cut-out Dimensions (H x W x D)	1298 x 226 x 100 mm 51,1 x 8.9 x 3.9 in
Weight	17.7 kg 39 lbs
Finish	White lacquer grille
Accessories	Manual Cut-out template

All technical specifications are subject to change without notice.

